

## DECK OIL

<b>Description</b>	Deck Oil is a specially selected mixture of modified natural oils. It is used mainly for maintaining and refreshing wood such as teak, mahogany, oregon, as well as all the bare wood. It is absorbed into the wood, saturating its pores without forming a film and acts as water repellent. It has great resistance to bad weather conditions and the intense sunlight and enhances the natural color and texture of wood. It is ideal for unvarnished garden furniture, boat and pool decks as well as for any wooden decorative objects of interior and exterior use. It is offered in transparent.	
<b>Technical Information</b>	Shade	Transparent
	Specific Weight	0,84-0,86 kg/lit (EN ISO 2811)
	Theoretical cover	10–15 m <sup>2</sup> /lit
	VOC	Ready to use maximum: 400g/lit EU LIMITS (2010): 700 g/lit SUBCATEGORY: f – minimal build wood stains, type S
<b>Drying Time (25°C)</b>	Touch Dry	2-3 hrs
	Recoating	24-48 hrs
	<i>(The above times are indicative and depend on the thinning percentage, moisture and temperature)</i>	
<b>Surface Preparation</b>	The surfaces must be clean, dry, without oil or dust and detached pieces. Old layers must be removed by mechanical means.	
<b>Application</b>	It must be applied directly on the wooden surface in order to achieve maximum penetration. It is applied directly without thinning with a brush, air pistol or immersion. After application remove the extra material with cloth or brush. For surfaces exposed to bad weather conditions, apply a second layer of deck oil.	
	Application temperature	10°C-35°C
	Suggested thinners	1124, 1015
	The choice of suitable thinner depends on the application method, the temperature and the humidity conditions. For the suitable choice, please contact with the technical department of our company	
	Clean application tools immediately with the suggested thinners.	
<b>Storage</b>	For 12 months in a dry and cool place (5-30°C)	
<b>Safety</b>	Please consult the Material Safety Data Sheet. Available upon request.	

This Technical Data Sheet replaces and cancels every previously issued.

The information, instructions, recommendations and specifications mentioned in this data sheet, represent the results and experience obtained from testing under controlled or specially adapted conditions.

The accuracy and relevance of these results to the actual conditions, in which you apply the product, must be determined and depend only on the purchaser and/or applicator.