

XYLOSOL EXTRA

Description	<p>Xylosol extra is a ready to use water-based wood preservative to protect wood such as windows, exterior doors, cladding, fencing, eaves, canopies, etc. It has proved to provide excellent protection of wood surfaces from fungi that cause rot and destruction of wood and from fungi that cause discoloration or cyanosis of wood and mold creation (blue stain) (in accordance with European Standard EN 152). In addition to these it protects from wood-eating insects and termites (Beetles-Termites) (in accordance with European Standard EN 46 after EN 84/EN 73 and EN 118 after EN 84/EN 73). It presents high adhesion and penetration, no peeling and no flaking as it does not form a skin on the surface.</p>										
Technical Information	<table border="0"> <tr> <td>Shade</td> <td>Transparent</td> </tr> <tr> <td>Specific Weight</td> <td>1,00 (±0,02) kg/lt (EN ISO 2811)</td> </tr> <tr> <td>Theoretical cover</td> <td>200 ml/ m²</td> </tr> <tr> <td>VOC</td> <td>25 g/lt</td> </tr> <tr> <td></td> <td>For professional use only</td> </tr> </table>	Shade	Transparent	Specific Weight	1,00 (±0,02) kg/lt (EN ISO 2811)	Theoretical cover	200 ml/ m ²	VOC	25 g/lt		For professional use only
Shade	Transparent										
Specific Weight	1,00 (±0,02) kg/lt (EN ISO 2811)										
Theoretical cover	200 ml/ m ²										
VOC	25 g/lt										
	For professional use only										
Drying Time (25°C, 60%RH)	<table border="0"> <tr> <td>Touch dry</td> <td>1-2 hrs</td> </tr> <tr> <td>Recoated</td> <td>24 hrs</td> </tr> <tr> <td>Full drying</td> <td>24-48 hrs</td> </tr> </table> <p><i>(The above times are indicative and depend on the thinning percentage, relative humidity and temperature)</i></p>	Touch dry	1-2 hrs	Recoated	24 hrs	Full drying	24-48 hrs				
Touch dry	1-2 hrs										
Recoated	24 hrs										
Full drying	24-48 hrs										
Surface Preparation	<p>The surfaces must be clean, dry, without oil or dust and detached pieces. Old layers must be removed by mechanical means.</p>										
Application methods	<p>It is suitable for professionals and for personal use. The product is ready to use (no thinning is required). Shake well before use.</p> <p>Do not apply during rain or when rain is expected during the next 24 hours from the application.</p> <p>It must be applied directly on the wooden surface in order to achieve maximum immersion. It is applied with brush or roller and the consumption suggested is: 200 ml / m² –for impregnation: at least 3 min.</p> <p>The product enhances the adhesion properties for subsequent surface coating.</p> <p>For better protection from sun radiation and weather conditions and for a better finish surface, a second appliance with wood stain STANCOLIN ή STANCOSOL or water based AQUASOL or YACHT VARNISH 182 is recommended.</p> <p>Not appropriate for use on wood in direct contact with the ground or the marine environment. Do not use on treated wood indoors except for the window frames and external doors. Do not use wood that comes into direct contact with food and animal feed.</p> <table border="0"> <tr> <td>Application Temperature</td> <td>5°C-35°C</td> </tr> <tr> <td>Application humidity</td> <td><80%</td> </tr> <tr> <td>Suggested thinners</td> <td>Water (for cleaning tools)</td> </tr> <tr> <td>Wood moisture</td> <td>< 12 % tough wood < 15 % soft wood</td> </tr> </table> <p>Clean application tools immediately with water. Close the container carefully and tightly after use.</p>	Application Temperature	5°C-35°C	Application humidity	<80%	Suggested thinners	Water (for cleaning tools)	Wood moisture	< 12 % tough wood < 15 % soft wood		
Application Temperature	5°C-35°C										
Application humidity	<80%										
Suggested thinners	Water (for cleaning tools)										
Wood moisture	< 12 % tough wood < 15 % soft wood										
Storage	<p>Recommended storage conditions: up to 24 months (dry and cool place 10°C - 25°C, without direct contact to sunlight, in ventilated space and locked away from children and food). Protect from frost. Keep the product only in its original container. Keep the container tightly closed.</p> <p>Do not store compositions in containers of iron or steel for prolonged periods. Metal</p>										

Safety

packaging for compositions should always be internally coated.

Wood preservatives must be used with care. Please read the product labels and instructions before using the product.

Common rules for safe working must be applied. Refer to the Material Safety Data Sheet before use and apply the product accordingly. Act only as described on the label.

Keep container tightly closed.

Cover the soil with a plastic sheet during an external application so as not to contaminate soil.

It should not apply when the product during application may reach surface waters, such as a bridge over the lake.

Wash any contamination from skin or eyes immediately. Wash hands and exposed skin before eating and after using.

Do not smoke or eat during application.

Keep in a safe place. Keep away from children. Keep away from sources of ignition - No smoking.

Do not contaminate water, food, or animal food by storage or disposal.

Wear appropriate protective clothing, gloves and eyes/face protection mask.

This Technical Data Sheet replaces and cancels every previously issued. The information, instructions, recommendations and specifications mentioned in this data sheet, represent the results and experience obtained from testing under controlled or specially adapted conditions. The accuracy and relevance of these results to the actual conditions, in which you apply the product, must be determined and depend only on the purchaser and/or applicator.